

Chapter - 27

From C to C++

Upgrading

There is a lot of C code out there. It is 95% compatible with C++.

That's why we're studying the other 5%.

K&R Style Functions

```
int do_it(char *name, int function) // C++ function definition
    {
    // Body of the function
```

```
int do_it(name, function) // Classic C definition
    char *name;
    int function;
    {
    // Body of the function
```

```
int funct(...); // Default prototype for class C functions
```

```
int do_it(); // Classic C function prototype
```

```
    i = do_it();
    i = do_it(1, 2, 3);
    i = do_it("Test", 'a');
```

enum, struct, union and class

C++

```
struct sample {  
    int i,j;    // Data for the sample  
};  
sample sample_var; // Last sample seen
```

C

```
struct sample sample_var; // Legal in C  
sample sample_var;       // Illegal in C
```

malloc and free

C's version of **new** is `malloc`:

```
foo_var = (struct foo *)malloc(sizeof(struct foo));  
           and calloc (calloc zeros the data)  
foo_var = (struct foo*)calloc(3, sizeof(foo));  
/* C++ uses      foo_var = new foo[3] */
```

C++ `malloc` trap:

```
class foo {...};  
foo_var = (struct foo *)malloc(sizeof(struct foo));  
// Don't code like this
```

WARNING: This creates the class without calling the constructor.

```
free((char *)foo_var);  
foo_var = NULL;
```

WARNING: This destroys the class without calling the destructor.

Turning Structures into Classes

Structure reading and writing

```
a_struct struct_var; // A structure variable

// Perform a raw read to read in the structure
read_size = read(fd, (char *)&struct_var, sizeof(struct_var));

// Perform a raw write to send the data to a file
write_size = write(fd, (char *)&struct_var, sizeof(struct_var));
```

Class reading and writing (NOT)

```
class sample {
public:
    const int sample_size; // Number of samples
    int cur_sample; // Current sample number
    sample(void) : sample_size(100) {} // Set up class
    virtual void get_sample(); // Routine to get a sample
};

sample a_sample;
// ...
read_size = read(fd, (char *)&a_sample,
                sizeof(a_sample)); // Very bad
```

Zeroing Structures and Classes

Clearing a structure

```
struct a_struct { ... }  
a_struct struct_var;  
// ...  
memset(&struct_var, '\0', sizeof(struct_var));
```

Clearing a class -- NOT!

```
class a_class { ... }  
a_class class_var;  
// ...  
memset(&class_var, '\0', sizeof(class_var));
```

setjmp

```
#include <setjmp.h>
```

```
int setjmp(jmp_buf env);
```

Where:

`env` is the place where `setjmp` saves the current environment for later use by `longjmp`.

Returns

0 Normal call

Non-zero

Non-zero return codes are the result of a `longjmp` call.

longjmp

```
void longjmp(jmp_buf env,  
            int return_code);
```

Where:

`env` is the environment initialized by a previous `setjmp` call.

`return_code` is the return code that will be returned by the `setjmp` call.

setjmp / longjmp usage

```
#include <setjmp.h>
#include <iostream>
```

3) Exception found
longjmp called to handle
emergency exit

```
jmp_buf location; // Place to store location data
```

```
void subroutine() {
    class list a_list;
    // Exception found, use
    longjmp(location, 5);
```

Code here is not executed
and this include the destructor for a_list

```
// This code is never executed
```

1) Normal setjmp call
(return value = 0)

```
int main() {
```

```
    if (setjmp(location) == 0) {
        std::cout << "Normal execution\n";
        subroutine();
```

2) Normal suborutine() call

```
    } else {
        std::cout << "Exception\n";
```

5) Exception handled

4) setjmp return
value=5 from longjmp

Turning C into C++

1. Change K&R style function headers into standard C++ headers.

2. Add prototypes.

3. Change `set jmp/long jmp` calls into **catch/throw** operations.

Following these two steps you have a C+1/2 program. It works, but it's really a C program in C++'s clothing. To convert it to a real C++ program you need to do the following.

4. Change `malloc` into **new**.

5. Change `free` into `delete` or **delete []** calls.

6. Turn `printf` and `scanf` calls into `std::cout` and `std::cin`.

7. When turning **struct** declarations into **class** variables be careful of `read`, `write` and `memset` functions that use the entire structure or class.